



Midea®			MSAB-24HRN1
Power supply		Ph-V-Hz	220-240V~ 50Hz, 1Ph
Cooling	Capacity	Btu/h	24000
	Input	W	2500
	Rated current	A	11.5
	EER	W/W	2.81
Heating	Capacity	Btu/h	26000
	Input	W	2370
	Rated current	A	10.9
	COP	W/W	3.22
Max. input consumption		W	4000
Max. current		A	20
Starting current		A	60
Compressor	Model		PA270G2CS-4MU1
	Type		ROTARY
	Brand		GMCC
	Capacity	Btu/h	23287/23458
	Input	W	2235/2385
	Rated current(RLA)	A	10.55/11.15
	Locked rotor Amp(LRA)	A	60
	Thermal protector		----
	Thermal protector position		INTERNAL
	Capacitor	uF	60
	Refrigerant oil/oil charge	ml	ESTEL OIL VG74 .850
Indoor fan motor	Model		RPG45C
	Input	W	77
	Capacitor	uF	3.0
	Speed((turbo)/Hi/Mi/Lo)	r/min	1120/1020/850
Indoor coil	a.Number of rows		2
	b.Tube pitch(a)x row pitch(b)	mm	21x13.37
	c.Fin spacing	mm	1.3
	d.Fin type (code)		Hydrophilic aluminium
	e.Tube outside dia.and type	mm	Φ7,innergroove tube
	f.Coil length x height x width	mm	820x336x26.74
	g.Number of circuits		4
Indoor air flow((turbo)/Hi/Mi/Lo)		m3/h	1065/955/760
Indoor noise level((turbo)/Hi/Mi/Lo)		dB(A)	49/44/39
Indoor unit	Dimension(W*D*H)	mm	1080x226x335
	Packing (W*D*H)	mm	1155x415x315
	Net/Gross weight	Kg	14/17.5



Outdoor fan motor	Model		YDK53-6C
	Input	W	136
	Capacitor	uF	3.0
	Speed (HI)	r/min	800
Outdoor coil	a.Number of rows		2
	b.Tube pitch(a)x row pitch(b)	mm	21x13.37
	c.Fin spacing	mm	1.4
	d.Fin type (code)		Hydrophilic aluminium
	e.Tube outside dia.and type	mm	Φ7,innergroove tube
	f.Coil length x height x width	mm	780x651x26.74
	g.Number of circuits		4
Outdoor noise level		dB(A)	59
Outdoor unit	Dimension(W*D*H)	mm	845x320x700
	Packing (W*D*H)	mm	965x395x755
	Net/Gross weight	Kg	49/52
Refrigerant type		g	R410A/1800
Design pressure		MPa	4.2/1.5
Refrigerant piping	Liquid side/ Gas side	mm(inch)	Φ9.52/Φ15.9(3/8"/5/8")
	Max. refrigerant pipe length	m	25
	Max. difference in level	m	10
Connection wiring			4x1.0(Optional)
Plug type			Outdoor supply
Thermostat type			Remote Control
Operation temperature		℃	17-30
Room temperature	Indoor(cooling/ heating)	℃	17-32/0-30
	Outdoor(cooling/heating)	℃	18-43/-7-24
Application area		m2	32-47
Qty'per 20' /40' /40'HQ			67/135/152



მოდელი			MUE-60HRN1
დენის წყარო		V-ph-Hz	380~415-3-50
გაგრილება	სიმძლავრე	Btu/h	55000
		kW	16.1
	მოხმარებული ელ.ენერგია	W	6400
	წომინალური დენი	A	10.5
	კოეფიციენტი EER :	W/W	2.52
გათბობა	სიმძლავრე	Btu/h	60000
		kW	17
	მოხმარებული ელ.ენერგია	W	5800
	წომინალური ძაბვა	A	9.6
	კოეფიციენტი COP :	W/W	3.03
შიდა ბლოკის ვენტილატორის ძრავი	მოდელი		YSK85-4C
	ბრენდი		2
	მოხმარებული ელ.ენერგია	W	120/110/105
	კონდენსატორი	uF	2.5uF/450V
	სიჩქარე (Hi/Med/Lo)	r/min	1315/1200/1120
შიდა ბლოკის თბომცვლელი	რიგების რაოდენობა		3
	მილის ბიჯი*რიგის ბიჯი	mm	21x13.37
	ფირფიტების ინტერვალი	mm	1.3
	ფირფიტების ტიპი		ჰიდროფილური ალუმინი
	მილის გარე დიამეტრი და ტიპი	mm	Φ7, შიდა ღარიანი მილი
	თბომცვლელის სიგრძე×სიმაღლე×სისქე	mm	1300x294x40.11
	კონტურების რაოდენობა		8
შიდა ბლოკის ჰაერის წაკადი (მაღ./საშ./დაბ.)		m^3/h	2300/1800/1600
შიდა ბლოკის ხმაურის დონე (მაღ./საშ./დაბ.)		dB(A)	55/49/46
შიდა ბლოკი	სუფთა ზომა(WxDxH)	mm	1650x675x235
	შეფუთული (WxDxH)	mm	1725x755x313
	სუფთა/სრული წონა	kg	39/45
საანგარიშო წნევა		MPa	4.2/1.5
დრენაჟის მილის დიამეტრი		mm	ODΦ25
ფრეონის მილები	თხევადი / აიროვანი	mm	Φ9.52/Φ19
მართვის პულტი			RG51Q1/BGE
ტემპერატურის დიაპაზონი		°C	17~30